



ELECTRONIC OFFICE TYPEWRITER

AE-610

NAKAJIMA ALL CO., LTD.

ELECTRONIC OFFICE TYPEWRITER AE-610

NAKAJIMA AE-610 INCREASES YOUR TYPING EFFICIENCY THROUGH USE OF THE MOST ADVANCED TECHNOLOGY.

FEATURES

MARGIN LEFT / RIGHT
MARGIN TOP / BOTTOM

SPACE
HALF SPACE
BACK SPACE
EXPRESS BACK SPACE
RELOCATION
INDEX FORWARD / REVERSE
MICRO UP / DOWN

PAPER INJECTOR

CORRECTION
WORD CORRECTION

PARAGRAPH INDENT

TAB (30 POSITION RESETABLE)
DECIMAL TAB

AUTO CENTERING
AUTO UNDERLINING (ALL, WORD)
BOLD TYPING
CAPS LOCK
REPEAT KEY

AUTO CARRIER RETURN
REQUIRED SPACE / HYPHEN

SPECIFICATIONS

PRINTING

PRINTING METHOD : PRINT WHEEL WITH 100 CHARACTERS
PRINTING SPEED : 20 CPS (MAX.)
PRINTING WIDTH : 11.5" (292mm)
PAPER CAPACITY : 15.0" (381mm)
PRINTING PITCH : 10, 12, 15, PS
LINE SPACING : 1, 1.5, 2
IMPRESSION CONTROL : L, M, H
NUMBER OF COPIES : 1 ORIGINAL + 4 COPIES

PRINTING RIBBONS

CORRECTABLE : 50 K
MULTI-STRIKE : 150 K

CORRECTION TAPES

LIFT-OFF : 1.7 K

KEYBOARD

PRINTING KEYS : 46
FUNCTION KEYS : 21
ROLL OVER SYSTEMS : 2-KEY ROLLOVER
KEYSTROKE BUFFER : 30 STROKES (MAX.)

TYPING MODES : NP

MEMORY

FORMAT MEMORY : 5 FILES (MAX.)
CORRECTION MEMORY : 10 LINES / 700 CHARACTERS (MAX.)

SPELL CHECK : OPTION

MAIN DICTIONARY : (U.S.A. / FRENCH -80,000 / 136,000 WORDS)
(U.S.A. / SPANISH -80,000 / 138,000 WORDS)

USER DICTIONARY : 300 WORDS

TECHNICAL DATA

W x D x H : 480 x 406 x 132 (mm)
(18.9" x 16.0" x 5.2")

WEIGHT : 7.8 kg

POWER SUPPLY : 100V / 50 - 60Hz
120V / 50 - 60Hz
220V / 50 - 60Hz
240V / 50 - 60Hz

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

NAKAJIMA ALL CO., LTD.

25-7, Hakozaiki-cho, Nihonbashi, Chuo-ku, Tokyo 103 Japan
Tel. (03)3669-2431 Fax (03)3669-2730 Telex 2524452

MAY 2005