

Embossers

Electric Embossing Machine



Compact heavy duty desktop embosser

- An up-to-date, highly economical seal embosser with enhanced operability and performance
- Replaceable embossing die block (seals available in diameters of 27, 36 and 45mm)
- Embossing dies can be simply rotated so that the seal can be embossed in one of four positions on the paper: top, right, left or bottom.

Model EEL-70

Features

- Whisper quiet operation (50dB)
- An up-to-date, highly economical raised (dry) seal embosser
- Minimal table top footprint; sturdy and reliable
- Uniformly clear impressions each and every time
- Automatically activated by inserting paper or via push button
- Paper insertion and position minimized with built in paper guides and back gauge



Recommended Applications

All vital & Official Documents:

- School & University Transcripts and Validations
- Government Seals: Assessor-Clerk-Recorder, Courts
- Vital Statistics: Birth, Death, Marriage & Health Departments
- Notary Public, Engineering & Architecture Firms
- Passport Control

[Die block]



S-27mm



M-36mm



L-45mm

Easily Replaceable Die Block (seals available in diameters of 27, 36 and 45mm)

Manual Embossing Machine



Model EML-110

Features

- Little efforts needed to achieve beautiful and clear impressions
- Throat depth can reach 110mm
It's possible to emboss in all positions of A4 size paper
- Compactness and weight light
- Security with key
- Embossing dies can be easily rotated and the seal can be embossed in top, right, left or bottom



[Die block]



S-27mm

M-36mm

L-45mm

Easily Replaceable Die Block (seals available in diameters of 27, 36 and 45mm)

Model	EES-70	EEM-70	EEL-70	EMS-110	EMM-110	EML-110
Maximum diameter of impression surface	27mm	36mm	45mm	27mm	36mm	45mm
Dimensions (mm)	94(W)x285(D)x785(H) (incl. table)			172(W) x237(D) x264(H) (When handle is up) 172(W) x281(D) x146(H) (When the handle is down)		
Weight	8kg			5.2kg		
Paper insert depth	Maximum 70mm from the center of seal			Maximum 110mm from the center of seal		
Power supply	Free voltage(100-240V)			-		
Power consumption	60w			-		
Rated time	Continuous rating			-		
Die block	Exchangeable (27/36/45)			Exchangeable (27/36/45)		